

Gas Poly/Steel/Stainless Hopper Salt & Sand Spreaders



SCH096SS Gas Stainless Steel Hopper Spreader



Hopper Sand & Salt Spreaders

PART NO.	DESCRIPTION	CAPACITY	CHUTE	SHIPPING WEIGHT
SCH072SS	72" Stainless Steel Hopper Spreader	1.3 cu. yds.	Std.	639 lbs.
SCH072SSX	72" Stainless Steel Hopper Spreader	1.3 cu. yds.	Ext.	655 lbs.
SCH096C	96" Carbon Steel Hopper Spreader	1.8 cu. yds.	Std.	857 lbs.
SCH096CX	96" Carbon Steel Hopper Spreader	1.8 cu. yds.	Ext.	875 lbs.
SCH096SS	96" Stainless Steel Hopper Spreader	1.8 cu. yds.	Std.	745 lbs.
SCH096SSX	96" Stainless Steel Hopper Spreader	1.8 cu. yds.	Ext.	758 lbs.
SCH120SS	120" Stainless Steel Hopper Spreader	2.3 cu. yds.	Std.	789 lbs.
SCH120SSX	120" Stainless Steel Hopper Spreader	2.3 cu. yds.	Ext.	804 lbs.

Hopper Sand & Salt Spreader Kits (Kits include Spreader, Inverted "V", Top Screen)

PART NO.	DESCRIPTION	CAPACITY	CHUTE	SHIPPING WEIGHT
1400200SS	72" Gas Stainless Steel Hopper Spreader Kit	1.3 cu. yds.	Std.	753 lbs.
1400250SS	72" Gas Stainless Steel Hopper Spreader Kit	1.3 cu. yds.	Ext.	764 lbs.
1400050	96" Gas Carbon Steel Hopper Spreader Kit	1.8 cu. yds.	Std.	945 lbs.
1400100	96" Gas Carbon Steel Hopper Spreader Kit	1.8 cu. yds.	Ext.	955 lbs.
1400050SS	96" Gas Stainless Steel Hopper Spreader Kit	1.8 cu. yds.	Std.	750 lbs.
1400100SS	96" Gas Stainless Steel Hopper Spreader Kit	1.8 cu. yds.	Ext.	760 lbs.
1400300SS	120" Gas Stainless Steel Hopper Spreader Kit	2.3 cu. yds.	Std.	873 lbs.
1400350SS	120" Gas Stainless Steel Hopper Spreader Kit	2.3 cu. yds.	Ext.	888 lbs.
1400400	96" Gas Poly Kit, Slide-In	1.8 cu. yds.	Std.	837 lbs.
1400450	96" Gas Poly Kit, Slide-In	1.8 cu. yds.	Ext.	853 lbs.

^{*} Truck Application is only a reference. The Gross Vehicle Weight (GVW) of the truck and calculated payload must be evaluated for each application.

GENERAL – All hopper spreaders are completely self-contained, ultra durable spreader units designed for ice and snow control. The rugged design allows for use with salt, sand and other materials. The complete assembly mounts easily on pickup, dump and platform trucks making it ideal for municipalities, shopping malls, industries, hospitals and private contractors. Available with poly, stainless steel, or steel hopper.

 $\begin{tabular}{ll} \textbf{CONVEYOR} - The conveyor is made of 12" wide all-steel pintle chain with 3/16"x 3/4" cross bars. Chain strength is 11,000 lbs. per strand; 22,000 lbs. total weight. \\ \end{tabular}$

ENGINE – Heavy-duty 10.5 horsepower Briggs & Stratton Intek industrial/commercial gasoline engine.

PART NO.	DESCRIPTION	SHIPPING WEIGHT
1492100	Utility Light	2 lbs.
1492110	LED Utility Light	1.1 lbs.

ELECTRIC THROTTLE CONTROL – In-cab throttle.

 ${f CLUTCH}-12$ volt DC electric clutch has a three-position in-cab switch.

72" SPREADERS – Capacity Struck, 1.3 cu. yd.; Capacity Rounded, 1.6 cu. yd.

96" SPREADERS – Capacity Struck, 1.8 cu. yd.;

Capacity Rounded, 2.1 cu. yd.

120" SPREADERS – Capacity Struck, 2.3 cu. yd.; Capacity Rounded, 2.7 cu. yd.



